



One Box Is All You Need.

Print. Copy. Fax. Scan.

The WorkCentre PE220 is big in performance and small in size making it suitable for small businesses and workgroups, branch offices and individual users.



Clean, efficient laser printing

Razor sharp copying

Great colour and monochrome scanning

Fully-featured fax capability



Consumables

Description Order Number

All-in-One Cartridge: CWAA0683
SmartKit® Print Cartridge 3K @5%

Capacities for 5% coverage on A4 size paper.
Printer is delivered with 1,000 pages of toner.

Configurations

WorkCentre PE220

Print	
Print speed	20ppm
First page out	11 seconds
Print Resolution	600 x 600 dpi
Processor/PDL GDI	GDI
Copy	
Copy speed	20cpm
First copy out	11 seconds
Print resolution	600 x 600 dpi
Copy features	2-up, 4-up, collation, auto-fit, clone, poster, multi-copy, ID card copy
Scan	
Scan resolution	600 x 600 dpi, up to 4800 x 4800 dpi enhanced
Fax	
Fax speed	3-second transmission speed at 33.6 Kbps
Resolution	203 x 98 dpi (Standard), 203 x 196 dpi (Fine/Photo), 300 x 300 dpi (Superfine), 200 x 200 dpi (Colour)
Paper Handling	
Paper input capability	150-sheet main tray, 1-sheet bypass tray
Automatic document feeder	30 sheets A4/Letter
Paper output	50 sheets, face down
General	
Supported O/S Printer Drivers	Windows 95, 98, ME, 2000, XP, Mac OS 10.3, Linux
Total memory	16MB
Connectivity	USB 1.1 (compatible with USB 2.0), IEEE 1284 Parallel
Duty Cycle	5,000 pages/month (maximum)
Included Software	PaperPort® SE 10.0, OmniPage® SE 3.0
Warranty	One year return to depot warranty*

Specifications

Print

Technology: Laser black-and-white
Memory: 10 MB

Scan

Compatibility: TWAIN standard (Windows 98, ME, 2K, Mac, Linux), WIA standard (Windows XP)
Depth: Colour: 24-bit
Mono: 1-bit for line art, halftone
Grayscale: 8-bit

Fax

Compatibility: ITU-T Group 3, ECM
Data Compression: MH/MR/MMR, JPEG (Colour)
Memory: 2 MB (approximately 160 pages)*

Media Handling

Input Paper Capacity
Main Tray: 150 sheets
Minimum size: 76 x 127 mm
Maximum size: 216 x 356 mm
Weight: 60 - 90 gsm
Bypass Tray: 1 sheet
Minimum size: 76 x 127 mm
Maximum size: 216 x 356 mm
Weight: 60 - 165 gsm
Document Handler: 30 Sheets
Width: 142 - 216 mm
Length: 148 - 356 mm
Weight: 60 - 90 gsm
Media Types: Plain paper, envelopes, labels, postcards, transparencies

Operating Environment

Temperature: Maximum Range: 10°C - 32°C
Recommended Range: 16°C - 30°C
Humidity: Maximum Range: 20 - 80%

Recommended Range: 30 - 70%
Electrical: Power: 220-240 VAC, 50/60 Hz, 2.5 A
Maximum Power Consumption: 350 watts
ENERGY STAR® compliant

General Specifications

Dimensions: 438W x 374D x 368H mm
Weight: 10.4 kg
Device Management: ControlCentre™ 5.0
All-in-One Cartridge: SmartKit® Print Cartridge 3k @ 5% ISO19752
Recommended Average Monthly Volume: Up to 750 pages
Safety Agency Approvals: UL Safety and ETL Semko

Customer Support

One year return to depot warranty, online web technical support and telephone support. Innovative service offerings include optional extended Service Agreements.

Warranty varies by location. For details please check with your local Fuji Xerox Printers office (AUS: 1800 811 177, NZ: 0800 449 177) or online at www.fxprinters.com.

* Based on CCIT No. 1 chart at standard resolution.
^ Return to Depot support nationally. The transportation of the faulty product to & from FXP is at the customer's expense. If the product fault is outside the 1 year warranty legislation, the product may be repaired at the customer's expense on a Time & Materials basis. Service labour charges for Return to Depot.

For more information or for your nearest authorised Fuji Xerox Printers reseller, visit our web site or call:

Australia 1300 793 769
New Zealand 0800 993 769

www.fxprinters.com



©2005 Fuji Xerox Printers. All rights reserved. Contents of this publication may not be reproduced without permission of Fuji Xerox Printers. Xerox, The Document Company, the stylised X, Phaser, CentreWare® and PhaserSmart® are registered trademark/trademarks of Xerox Corporation. All other names mentioned are trademarks of their respective companies. The information in this brochure is subject to change without notice. Errors and omissions excepted.

Fuji Xerox Printers practice a policy of continued product development, this means that product specifications may incorporate innovations and/or enhancements resulting from ongoing research & development (and may vary from those specified in brochures at time of printing). In keeping with normally accepted commercial practices, the purchaser is advised to both confirm product specifications, and satisfy themselves as to product performance and exact configuration (to suit each particular requirement) before purchase. Fuji Xerox Printers will not accept any liability (product related and/or resulting from product usage) where such due diligence has not been performed and the incorrect product has been purchased. WCP220_140525231v_0723